



LEAD THE CHANGE

WITH **3523R (8×2)**



Technical Specifications

Vehicle Dimensions			
Wheel Base (mm)	5775	6375	6375
Cabin	Sleeper	Sleeper	Compact Sleeper
Loading Span (ft)/	·	•	
Loadbody cpc (Cu.m)	26ft	28ft	32ft
Overall Length (mm)	10492	11092	11992
Overall Width (mm)	2490	2490	2490
Overall Height (mm) (CBC)	2960	2960	2960
Front Overhang (mm)	1485	1485	1485
Rear Overhang (mm)	2557	2557	3457
Ground Clearance (mm)	233mm	233mm	233mm
Engine			
Engine Model	OM 926		
Maximum Power, KW	180Kw @2200 rpm		
Maximum Torque, Nm	850 Nm @ 1200 - 1600 rpm		
No. of Cylinders, CC	6, 7200		
Emission Std	Bharat Stage VI		
Transmission			
Gear Box Model & Type	Improved G85, 6F+1R, Mechanical,	Synchromesh Gears	
Clutch Type	Single Dry Plate, Hydraulic Control		
Clutch Dia, (mm)	395, 4 mm		
Axle	.== .		
Front Axle	IF 7.0		
Rear Axle	RA 1:IR440-11 & RA2: IT- 10		
RAR*	5.875		
Chassis Frame & Suspension			
Frame Section (D X W X T) (mm)	286 x 70 x 8		
Front Suspension	Parabolic Type Leaf Spring with 2 H		
Rear Suspension	Balancer Type Semi-Elliptical Leaf S	. •	
Anti-Roll Bar	Front: Standard, Rear applicable for: High Centre of Gravity (HCG)	Front: Standard, Rear applicable for: Hazards Goods Pack (HGP) & High	Front: Standard, Rear applicable for: High Centre of Gravity (HCG)
	g comis or crainly (100)	Centre of Gravity (HCG)	g com c c c.a, (c.,
Brakes	5	ABO	
Service Brake	Pneumatic, Foot Operated, Dual Lin	e with ABS	
Parking Brake	Pneumatically Operated Hand Control Valve		
Front Axle Brake	Ø 410 drum		
Rear Axle Brake	Ø 410 drum		
Steering			
Steering Type	Hydraulic Power Assisted		
Fuel Tank & Electricals			
Fuel Tank /	Standard - 380L/355L; HGP tanker -	200L/185L	
Filling Capacity*	601 /541		
Adblue Tank Battery Capacity	60L/51L 120Ah (Std)/130Ah (For HAP)		
Voltage	24V		
Performance	24 V		
Maximum Gradeability %	18.50%		
Maximum Geared Speed			
kmph	80 kmph (std)/60 kmph(POL tanker)		
TCD*	21.6m	23.7m	23.7m
Tyres (Size, Pattern)			
Pattern and Size	Radial Tyres (Rib & Lug Pattern - 11R20 or 295/90R20) Tubeless Tyres (All Wheel Pattern - 295/80R22.5) Tubeless Tyres (Rib & Lug Pattern - 295/80R22.5)		
Weight			
Gross Vehicle Weight - GVW	35000 kgs (Tubeless tyres & 295/90F	R20), 34920 kgs (11R20)	

Dealer Stamp